



LuxStone SEALER

PRODUCT NAME: Luxstone Sealer

PRODUCT NUMBERS: LS5 / LS1

DESCRIPTION: A protective clear coat for porous stone, brick and most cement surfaces where minimal sheen and enhancement is desired.

SUGGESTED USES: Use on all porous stone and limestone surfaces, travertine, pavers, brick, and decorative finishes.

ADDITIONAL USES: Blasted marble, paver stones, slate and concrete.

COLOR: Clear

FINISH: Matte or Semi-gloss

VEHICLE TYPE: Water based

SOLVENT TYPE: Water

VOC: < 50 gm/l

DRY TIME: 1 to 2 hours at 70 degrees / 50% relative humidity

SOLIDS BY WEIGHT,%: 27 % +/- 3%

COVERAGE: Coverage averages on porous surfaces: **Rolling** - 300 sq. ft per gallon. **Spraying** – 400 sq. ft. per gallon.

RECOMMENDED DRY TIME: At 70°F and 50% relative humidity: **Touch** – 1 to 2 hours (depending on weather). **Recoat** – 3 to 6 hours. Surface will be tack free in 3 to 6 hours, ready for foot traffic in 12 to 24 hours and vehicle traffic in 72 hours. Dry times may vary depending on air temperature, wind, and humidity.

LIMITATIONS: CAUTION: DO NOT apply in temperatures below 50°F. DO NOT apply to a puddling surface. On excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly. If this condition exists we recommend a light misting of the surface with plain water.

SURFACE PREPARATION: Pavers must be clean, **dry** and free of any dirt, stains, and failed sealer. Testing of the surface is recommended to insure desired results.

(LuxStone Sealer Cont'd)

MIXING: Stir gently for 1 minute with bottom-up strokes.

APPLICATION: Brush, Roller (3/8" nap), or spray. DO NOT APPLY excessive pressure on the roller, roll with light to medium pressure. Apply sealer evenly and try to minimize puddles or roller trails. Only one coat is required. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness – DO NOT APPLY THIS PRODUCT. If there is a possibility of slipperiness, non skid additives should be used.

PACKAGING: 1 gallon, 5 gallon

Limitations / precautions:

Keep out of reach of children. Do not take internally. Applicators should wear protective eyewear, gloves and NIOSH mask if spraying. If swallowed, contact a physician immediately.

Limitation of Liability: Technical data is true and accurate to the date of issuance but not subject to change without notice. Our products conform to our quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, equipment or consequential damages are excluded.