



6010 N. Powerline Road, Ft. Lauderdale, FL 33309
954-772-0300 • acrylux.com

PRODUCT DATA

COLORBACK PAVER SEALER

- PRODUCT NAME:** Colorback Paver Sealer
- PRODUCT NUMBERS:** CB5, CB1
- DESCRIPTION:** A protective clear coat and curing compound for concrete brick pavers.
- SUGGESTED USES:** A semi-gloss finish coat for concrete brick pavers.
- ADDITIONAL USES:** Concrete curing compound, concrete chatahoochee.
- COLOR:** Clear
- FINISH:** Semi-Gloss
- VEHICLE TYPE:** Solvent acrylic
- SOLVENT TYPE:** Xylene
- VOC:** gm/l 692
- FLASH POINT:** 81°F
- SOLIDS BY VOLUME, %:** 25.5 %
- SOLIDS BY WEIGHT, %:** 29.84 %
- WEIGHT PER GALLON:** 7.74 lbs.
- COVERAGE:** Coverage averages on porous surfaces: **Rolling** - 200 sq. ft per gallon. **Spraying** – 300 sq. ft. per gallon.
- RECOMMENDED DRY TIME:** At 70°F and 50% relative humidity: **Touch** – 1 hour (depending on weather). **Recoat** – 2 hours. Surface will be tack free in 1 hour, ready for foot traffic in 2 hours and vehicle traffic in 72 hours. Dry times may vary depending on air temperature, wind, and humidity.
- LIMITATIONS:** CAUTION: DO NOT apply in temperatures below 50°F. DO NOT apply to a damp surface. On excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly, causing trapped vapors to bubble. If this occurs we recommend application during a cooler time of day.
- SURFACE PREPARATION:** Pavers must be clean, dry and free of any dirt, stains, and failed sealer. On bare concrete, the surface must be clean and dry.

MIXING: Stir from bottom with vigorous strokes. Do not add oil or other paints. DO NOT add Xylene or other solvents. DO NOT thin.

APPLICATION: Brush, Roller (min 3/8" nap), or airless spray. DO NOT APPLY excessive pressure on the roller, roll with light to medium pressure. Apply paver sealer evenly and do not leave puddles or roller marks. Only one coat is required. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness – DO NOT APPLY THIS PRODUCT. If there has been a skid texture added to the base coat this product may perform properly but all precautions must be taken.

SHELF LIFE: 2 years

PACKAGING: 1 gallon, 5 gallon

DOT: Not regulated

SAFETY INFORMATION: *EXTREMELY FLAMMABLE – CONTAINS STRONG SOLVENTS.* Use with adequate ventilation. Avoid breathing vapors and mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (MOSH/MSHA TC23C or equivalent) or leave the area. Do not ingest. Avoid contact with the skin. Wash immediately after use and before smoking and eating. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. Keep away from direct heat, sparks, and open flame. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead.

Revision: 12/02/06