



TECHNICAL DATA SHEET

Product Name:	Luxstone Natural Stone Sealer
Product Numbers:	LS1, LS5
Description:	A protective clear coat for porous natural stone, brick and most cement surfaces where minimal sheen and enhancement is desired.
Suggested Uses:	For use on all porous natural stone, travertine, pavers, bricks, and decorative finishes.
Colors:	Clear
Finish:	Matte or Semi-Gloss
Vehicle Type:	Acrylic
Solvent Type:	Water
VOC:	<50 gm/l
Flash Point:	Non-Flammable
Solids by Volume:	27% +/-
Weight Per Gallon:	9 lbs. per gal. +/-
Coverage:	Theoretical coverage is 400 - 500 square feet per gallon (rolling) and 300-400 square feet (spraying) depending on surface porosity. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.

Recommended Dry Time:	At 70 F and 50% relative humidity: Dry to touch in 1-2 hours (depending on weather). Recoat in 3 to 6 hours. The surface will be tack free in 3 to 6 hours, ready for foot traffic in 12 to 24 hours and vehicular traffic in 72 hours. Dry times may vary depending on air temperature, wind, and humidity.
Surface Preparation:	The surface must be clean, dry, and free of any dirt, stains, and failed sealer. Testing of the surface is recommended to ensure desired results.
Mixing:	Stir well and apply as it comes from the container.
Application:	Apply using a brush, roller (3/8" nap), or sprayer. DO NOT APPLY excessive pressure on the roller, roll with light to medium pressure. Apply sealer evenly and try to minimize puddles or roller trails. Only one coat is required. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness – DO NOT APPLY THIS PRODUCT. If there is a possibility of slipperiness, non skid additives should be used. Surface should be dry for 24 hours before application.
Packaging:	1 Gallon, 5 Gallon
Shelf Life:	2 Years
Safety Information:	Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead .