



TECHNICAL DATA SHEET

Product Name:	Acrylux Masonry Patch Textured
Product Numbers:	MPK1, MPK5, MPB1, MPB5
Description:	A textured elastomeric patching compound available in knife and brush grade.
Suggested Uses:	For use on exterior walls, stucco, banding, brick, roof tiles and all other masonry surfaces. Also for use as a tile fill compound. Recommended for repairing and maintaining the Acrylux Waterproofing System, caulking seams in corrugated and standing seam metal roofs, and asphalt shingle tab sealing.
Colors:	Off-White
Finish:	Smooth
Vehicle Type:	Elastomeric
Solvent Type:	Water
VOC:	75 gm/l
Flash Point:	Non-Flammable
Weight Per Gallon:	11 Pounds
Specific Gravity:	1.3
Thickness:	3/16"
Coverage:	Varies according to application and crack widths.
Viscosity:	Gun grade

Recommended Dry Time:	4 to 6 hours in direct sunlight; dry times may vary depending on air temperature, wind, humidity and applied thickness.	
Limitations:	Not for use under ponding water or below grade applications. Not for rusted surfaces.	
Surface Preparation:	For masonry: Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Seal any remaining chalk with Acrylux 3 to 1 Sealer.	
Mixing:	No mixing necessary.	
Application:	This product is a thick elastomeric patch, and can be applied by a brush or putty knife. Once the patch is applied to the surface, use a brush or a knife to spread the masonry patch evenly over the crack. For best results, open up or v-out cracks when using this product. Always test the finish coat for bleed-through or prime all patched areas. Some shrinkage may occur, a second layer may be required for a flush repair.	
Shelf Life:	2 Years	
Packaging:	1 Gallon, 5 Gallon	
Mechanical Properties:	Test Temperature:	76 F
	Tensile Strength (max stress) lbs/sq. in:	111
	Tensile Strength (break) lbs/sq. in:	125
	% Elongation (max stress):	950
	% Elongation (Fail):	1025
	% Recovery after 25% elongation:	90