

# **TREAD-FLEX**

- PRODUCT NAME:** Acrylux Tread-Flex
- PRODUCT NUMBERS:** TF1, TF5
- DESCRIPTION:** A high build pedestrian grade coating designed to bridge substrate cracks, fill imperfections and prevent water intrusion
- SUGGESTED USES:** Use on concrete balconies, cement roof tops, catwalks, flat decks with positive drainage, brick, wood, and seamless floor surfaces
- APPLICATION SUBSTRATE:** Excellent adhesion to a wide wall substrates including: concrete, masonry, metal, stone, wood, and roofing material
- COLORS:** White to medium value colors
- FINISH:** Satin-Flat (a low angular sheen) with medium granular texture
- VEHICLE TYPE:** 100% acrylic/elastomeric
- SOLVENT TYPE:** Water
- COATING VOC:** 75 G/L
- FLASH POINT:** Non-flammable
- TOTAL VEHICLE BY VOLUME:** 51.2 %
- TOTAL VEHICLE BY WEIGHT:** 64.8 %
- RECOMMENDED WET FILM:** 25 – 30 mils
- RECOMMENDED DRY FILM:** 15 mils
- COVERAGE:** Theoretical coverage at 15 mils is 75 - 100 sq. ft per gallon. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.
- VISCOSITY:** 120 to 140 ku
- RECOMMENDED DRY TIME:** 2 hours in direct sunlight; dry times may vary depending on air temperature, wind, and humidity. 6 – 8 hours for light traffic. 72 hours for heavy traffic
- LIMITATIONS:** Not for use under heavy ponding water or below grade applications.
- RECOMMENDED PRIMERS:** Acrylux AC64

(Tread-Flex Cont'd)

**SURFACE PREPARATION:** Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Seal any remaining chalk with AC64 primer/sealer

**MIXING:** Stir well and apply as it comes from the container. Box all colors to insure color uniformity.

**APPLICATION:** Brush, Roller (min 3/4" nap).

**SHELF LIFE:** 2 years

**PACKAGING:** 1 gallon, 5 gallon

**SAFETY INFORMATION:** Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).