



TECHNICAL DATA SHEET

Product Name:	UL200 Pigmented Primer/Sealer
Product Numbers:	UL2001, UL2002, UL2005
Description:	A 100% acrylic pigmented primer-sealer for new and previously painted masonry. A full body, high solids, alkali-resistant, water-based formulation.
Suggested Uses:	A primer coat for slightly chalky surfaces, masonry, stucco, previously painted wood, brick, cement tile, aluminum, primed metal, and all previously painted surfaces. UL200 can be used as a hot primer on fresh stucco.
Colors:	Tintable White
Finish:	Flat
Vehicle Type:	Acrylic
Solvent Type:	Water
VOC:	< 82 gm/l
Flash Point:	Non-Flammable
Solids by Volume:	36%
Weight Per Gallon:	8.76 Pounds +/-
Specific Gravity:	1.06
Recommended Wet Film:	2 mils
Recommended Dry Film:	1.5 mils
Viscosity:	90-92 ku

Coverage:	Coverage depends on surface texture, thickness of application, and porosity. The average coverage on most surfaces is approximately 300 sq. ft. per gallon.
Recommended Dry Time:	1 to 2 hours at 70 F and 50% relative humidity. Dry times may vary depending on air temperature, wind, and humidity.
Surface Preparation:	For masonry: Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Do not apply to heavily chalked surfaces. For metal: When used as a DTM primer rusted or raw steel must be primed with a rust inhibitive primer and rust must be removed or treated. For wood: Acrylux UL200 can be used over most previously painted wood; prime any staining wood with a stain blocking primer.
Mixing:	Stir well and apply as it comes from the container. Box all colors to ensure color uniformity.
Application:	Apply with a Brush, Roller (min $\frac{3}{4}$ nap), or airless sprayer. Recommended tip size: .015 to .019. UL200 is a light body primer designed to penetrate and should not be applied too heavily.
Packaging:	1 Gallon, 2 Gallons, 5 Gallons
Shelf Life:	2 Years
Safety Information:	Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead .