



TECHNICAL DATA SHEET

Product Name:	Acrylux Enviro-Premium Gloss Interior Paint
Product Numbers:	IG1, IG5, IGWC1, IGWC5
Description:	A high build, 100% acrylic latex interior wall and trim paint. A premium quality low odor and low VOC interior paint.
Suggested Uses:	A semi-gloss low odor finish coat for interior drywall, masonry, stucco, wood, brick, cement tile, aluminum, primed metal and all previously painted interior surfaces.
Colors:	Bright white, pearl white, and bases for 3000 custom colors.
Finish:	Semi-Gloss
Vehicle Type:	Spherical and lobed acrylic polymer
Solvent Type:	Water
VOC:	<50 gm/l
Flash Point:	Non-Flammable
Solids by Volume:	36.87% +/-
Solids by Weight:	53.13% +/-
Weight Per Gallon:	12.01 lbs. +/-
Recommended Wet Film:	4 mils
Recommended Dry Film:	1.5 mils
Viscosity:	95 ku

Coverage:	Theoretical coverage at 3 mils is 250 square feet per gallon. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.
Recommended Dry Time:	1 to 2 hours; dry times may vary depending on ambient conditions and temperature.
Surface Preparation:	<p>For Drywall: Remove all loose paint, dirt, mildew, foreign matter and chalk as to obtain a clean paintable sound surface. Seal any remaining chalk with Acrylux 3 to 1 Sealer.</p> <p>For Metal: May be applied directly to previously painted aluminum and galvanized steel with light sanding. All other applications to metal require an appropriate primer.</p> <p>For Wood: Prime new wood with appropriate latex primer and prime any staining wood with a stain blocking primer.</p>
Recommended Primer:	Acrylux 3 to 1 Sealer, Acrylux UL200 Pigmented Hot Stucco Primer, or any high quality latex or alkyd primer.
Mixing:	Stir well and apply as it comes from the container. Box all colors to ensure color uniformity.
Application:	Brush, Roller (Min 3/16" nap) or airless spray. Recommended tip size: .013 to .015.
Packaging:	1 Gallon, 5 Gallon
Shelf Life:	2 Years
Limitations	Not for use under ponding water or below grade applications.
Safety Information:	Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead .