

ENVIRONMENTALLY FRIENDLY INTERIOR FINISH

Enviro-Premium

certified clean green

A LOW ODOR, LOW VOC, INTERIOR PAINT
HIGH PERFORMANCE PRESERVES INDOOR AIR QUALITY MOLD RESISTANT



SMOOTH FINISH EXCELLENT HIDING STAIN RESISTANT EXCEPTIONAL WASHABILITY

ECO-FRIENDLY
ACRYLUX TOUGH



6010 POWERLINE ROAD FORT LAUDERDALE, FL 33309

(954) 772-0300

WWW.ACRYLUX.COM

ENVIRO-PREMIUM FLAT

PRODUCT NAME: Enviro-Premium Flat

PRODUCT NUMBERS: IP1, IP5, IPWC1, IPWC5

DESCRIPTION: A high build, 100% Acrylic Latex interior wall and trim paint. Low odor and low VOC.

SUGGESTED USES: A flat low odor finish coat for interior drywall, masonry, stucco, wood, brick, cement tile, aluminum, primed metal and all previously painted interior surfaces.

COLORS: Bright white, pearl white, and bases for 3000 custom colors.

FINISH: Flat, (0-5 @ 85)

VEHICLE TYPE: Spherical and lobed acrylic polymer

SOLVENT TYPE: Water

VOC: gm/l < 50

FLASH POINT: Non-flammable

SOLIDS BY VOLUME: 32.77 %

SOLIDS BY WEIGHT: 53.14 %

WEIGHT PER GALLON: 12.01 lbs. / Gal

RECOMMENDED WET FILM: 4mils

RECOMMENDED DRY FILM: 1.5 mils

COVERAGE: Theoretical coverage at 3mils is 250 sq. ft per gallon. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.

VISCOSITY: 95 ku

RECOMMENDED DRY TIME: 1 to 2 hours; dry times may vary depending on ambient conditions and temperature.

LIMITATIONS: Do not apply in temperatures below 50F or 10C

RECOMMENDED PRIMERS: Self-priming for most applications. Multi-purpose latex, Quick dry oil, any primer recommended for latex topcoats.