



TECHNICAL DATA SHEET

Product Name:	Acrylux Masonry Patch Smooth
Product Numbers:	MPKS1, MPKS5, MPBS1, MPBS5
Description:	A smooth elastomeric patching compound.
Suggested Uses:	Patching roofs, exterior walls, stucco, roof tile, banding, brick, all other masonry surfaces, and as a tile fill compound. Recommended for repairing and maintaining the Acrylux Waterproofing System, caulking seams in corrugated and standing seam metal roofs, and asphalt shingle tab sealing.
Colors:	Off-White
Finish:	Smooth
Vehicle Type:	Elastomeric
Solvent Type:	Water
VOC:	75 gm/l
Flash Point:	Non-Flammable
Weight Per Gallon:	11 Pounds
Specific Gravity:	1.3
Thickness:	3/16"
Coverage:	Varies according to application and crack widths.
Viscosity:	Gun grade

Recommended Dry Time:	4 to 6 hours in direct sunlight; dry times may vary depending on air temperature, wind, humidity and applied thickness.	
Limitations:	Not for use under ponding water or below grade applications. Not for rusted surfaces	
Surface Preparation:	For masonry: Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Seal any remaining chalk with AC64 primer/sealer.	
Mixing:	No mixing Necessary.	
Application:	This product is a knife grade and may be applied by gun or putty knife. To apply by knife, scoop Roof Caulk with a putty knife and apply to surface. Once caulk is applied to the surface, trowel to desired finish height and texture. It is advisable to V-cut cracks when using this product; however, joint tape may reinforce some larger repairs.	
Shelf Life:	2 Years	
Packaging:	1 Gallon, 5 Gallon	
Mechanical Properties:	Test Temperature:	76 F
	Tensile Strength (max stress) lbs/sq. in:	111
	Tensile Strength (break) lbs/sq. in:	125
	% Elongation (max stress):	950
	% Elongation (Fail):	1025
	% Recovery after 25% elongation:	90