

Tint Seal Roof Application Instructions

1. Pressure clean the entire roof to remove dirt, mildew, and foreign material. Lightly rinse the roof with Clorox solution and rinse after 1/2 hour. Allow 24 hours of dry time to proceed.
2. Allow the roof tiles to dry before applying Tint-Seal. For the best results, do not apply Tint-Seal to a wet or damp surface. Dry times vary depending on air temperature, wind, and humidity. Do not apply below 55 degrees Fahrenheit.
3. We recommend mixing 1 Quart of colorant into each 5-gallon pail of Tint-seal. Please test your mixing ratio on an inconspicuous area of the roof before sealing the entire area. Add LESS than 1 Quart of colorant for MORE transparency. Add MORE than 1 Quart of colorant for LESS transparency.
4. Mix the dedicated colorant package in the sealer for two (2) minutes directly before use. Stir occasionally to ensure color uniformity.
5. To achieve the best results, we recommend applying Tint-Seal with an airless sprayer. Recommended tip size: .023 - .039. Recommended pressure: Low - Medium. If a pump sprayer is being used, ensure that it reaches full atomization to prevent puddling or over application. It is important that the machine can produce an even, consistent fan and complete full courses.
6. Begin at the peak of the desired area and spray full courses from one side to the other, achieving a minimal overlap on each pass. If you must stop spraying before the entire area is covered, stop on a hip, valley, or edge.
7. Be sure to angle the sprayer wand to cover the leading edges of the tile for complete coverage.
8. If additional color is desired. Apply a second coat after two (2) hours.

**SCAN QR CODE TO VIEW
PROPER SPRAYING
TECHNIQUE**



**SCAN QR CODE TO VIEW
THE ROOF CUSTOM
COLORS CHART**

