



ColorBack Horizontal Hard Surface Stripper

PRODUCT NAME: ColorBack Horizontal Hard Surface Stripper

PRODUCT NUMBERS: CBS1, CBS5

DESCRIPTION: **ColorBack Horizontal Hard Surface Stripper** is a water-based environmentally friendly, low-odor stripper designed to remove up to five layers of latex, acrylic, urethane, varnish, lacquer, floor finish build-up, adhesive, lead-based paint, and architectural and industrial coatings. This stripper is ideal for stripping pool decks, driveways, walkways, and patios. This product does not contain any methylene chloride, methanol, NMP, petroleum distillates or caustic.

SUGGESTED USES: For use on pavers, natural stone, brick, concrete, wood, and metal.
**Always apply a test patch to determine the suitability, compatibility, dwell time, coverage, and desired results. **

PROPERTIES:

Appearance	White, viscous
Odor	mild, sweet
Flash Point	>204 degrees Fahrenheit (benzyl)
pH	10
lbs./gallon	9.3

COVERAGE: Coverage varies depending on the surface the stripper is applied to, product being removed, and the application method, but is generally between 100-250 square feet per gallon.

ACTIVE INGREDIENT: Alcohol Base

SOLVENT TYPE: Water

ACTIVES BY VOLUME: +50%

RECOMMENDED DRY TIME: Between 5 and 30 minutes

LIMITATIONS: Excessive runoff may harm grass and vegetation.

(ColorBack Horizontal Hard Surface Stripper Cont'd)

- SURFACE PREPARATION:** Before applying the stripper, ensure that all areas not being are fully protected. The surface being stripped should be completely dry before application as a wet surface will decrease the effectiveness of the stripper. Ideally, the surface temperature should be between 55 degrees and 100 degrees.
- APPLICATION:** This stripper can be applied using a brush, roller, or sprayer. Apply the product liberally leaving a layer 20-30 mils thick. After the stripper is applied, a dwell time of 5-30 minutes will remove most paver coatings. Plastic can be used to cover the active stripper to increase the dwell time and stripping action. Once the coating has softened and lifted, remove using a pressure washer and surface cleaner. Lifted sealer can also be removed by scraper, stiff bristle brush and garden hose. Thoroughly rinse the surface to remove any residue and collect all debris for proper disposal.
- CLEAN UP:** Clean up all applicators and equipment with soap and water or denatured alcohol. Do not store or collect remover and/or paint residue in metal containers. Use plastic containers only.
- SHELF LIFE AND STORAGE:** Ensure that the container is closed after each use. Keep away from any heat sources or open flames. Protect from freezing. Shelf life is infinite in its original closed containers stored at ambient temperatures.
- PACKAGING:** 1 gallon, 5 gallon
- SAFETY INFORMATION:** SEE SDS SHEET