



Safety Data Sheet

Section 1: Identification of the Product/Company

Product Identifier:

Product Name: COLORBACK HSS STRIPPER

Product Code:

Relevant identified uses of the substance or mixture

Recommended use:

For professional use in the construction industry as a COATINGS REMOVER

Uses advised against:

None identified, use only as stated on the label

Details of the supplier of the safety data sheet

Manufacturer:

Acrylux Paint Manufacturing Company Private Label
6010 Powerline Road
Fort Lauderdale, FL 33309-2014
United States

Telephone (General) (954) 772-0300

Emergency telephone number

Manufacture: (954) 772-0300 USA

Section 2: Hazards Identification

Classification of the substance or mixture

This material is not classified as hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200

GHS-US classification

No need for classification according to GHS criteria for this product

Label elements

GHS-US labeling

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards

No other information available

Unknown acute toxicity (GHS-US)

No data available

Precautionary statements (GHS-US)

Prevention:

P264 Wash thoroughly after handling

Section 3: Composition/information on ingredients

Substances

There are no hazardous components above the relevant concentration limits according to OSHA HazCom 2012.

Name	Product Identifier	% by weight	GHS-US classification
Benzyl Alcohol	100-51-6	40-50%	
Monoethanolamine	141-43-5	1-5%	

This product contains an amine neutralizing agent which is bound in the matrix of this product as a salt. The amine salt is considered essentially unreactive at room temperature. Generation of amine vapors is expected when this product is processed (heated) during the drying / hardening of the coating.

Section 4: First aid measures

Description of necessary first aid measures

First-aid measures general:

Remove contaminated clothing

First-aid measures after inhalation:

If affected, remove to fresh air. Assist in breathing if necessary

First-aid measures after skin contact:

Immediately remove contaminated clothing and shoes. Launder clothing before reuse. Seek medical attention if symptoms of irritation or burns occur.

First-aid measures after eye contact:

Flush with copious amount of water for at least 15 minutes. If irritation develops, seek medical attention.

First-aid measures after ingestion:

Do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth to an unconscious or convulsing person. If person is conscious, rinse out the mouth with water and give plenty of water to drink. Get medical attention immediately.

Most important and effects, both acute and delayed

Symptoms:

None expected due to the non-classification of the product.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

Section 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO₂), Dry chemical, Foam, water spray for large fires

Unsuitable extinguishing media:

None known

Special hazards arising from the substance or mixture

Fire hazard:

By Fire and Thermal Decomposition: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke, Isocyanate, Isocyanic Acid and other undetermined compounds., Hydrogen cyanide

Explosion hazard:

Non-explosive

Reactivity:

Will not facilitate or support combustion of other materials.

Advice for firefighters

Firefighting instructions:

Not required

Protection during firefighting:

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture.

Additional information

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures:

Wear protective equipment as described under Section 8 and follow the advice of safe handling and use given under Section 7. Emergency procedures are not required.

For non-emergency personnel

Protective equipment:

Wear chemical resistance (impervious) gloves

Emergency procedures:

High risk of slipping due to spillage/leakage of product

For emergency responders

Protective equipment:

Not Applicable

Emergency procedures:

Not Applicable

Environmental precautions

Do not allow to enter drains, sewers or watercourses.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, etc.). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off products

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protective equipment

See Section 13 for disposal information

Section 7: Handling and storage

Precautions for safe handling

Precautions for safe handling:

Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation.

Hygiene measures:

General occupational hygiene measures are required to ensure safe handling of the product. These measures involve good personal and house-keeping practices. Wash hands after use if contaminated. Avoid wearing contaminated clothing. In dusty environment, wear dust mask, protective goggles and gloves.

Conditions for safe storage, including any incompatibilities

Storage conditions:

Store protected against freezing

Incompatible products:

See section 10

Incompatible materials:

See section 10

Storage area:

The product should be stored in a cool, dry and well-ventilated area, at ambient temperature directly out of the sunlight.

Section 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits:

Chemical Name	CAS #	EXPOSURE LIMITS
Benzyl Alcohol		10 ppm TWA AIHA TLV
Monoethanolamine		3 mg/m ³ TWA ACGIH TLV 6 mg/m ³ STEL ACGIH TLV 3 mg/m ³ TWA OSHA PEL

Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation

Personal protective equipment:

Wear protective goggles and gloves with repeated and prolonged exposure. Wear respiratory protection in a poor ventilated environment.

Hand protection:

Permeation resistant gloves, Butyl rubber gloves, Nitrile rubber gloves

Eye protection:

Chemical goggles or ANSI safety glasses with side-shields should be worn especially in a splashing environment. Use of contact lenses solely is not recommended.

Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate NIOSH certified respirators.

Thermal hazard protection:

Wear suitable protection clothing

Other information:

Employees should wash their hands and face before eating, drinking, or using tobacco products.

Educate and train employees in the safe use and handling of this product. Store separate from food products.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Thixotropic
Color:	Milky White
Odor:	Very faint
Odor threshold:	Not available
pH:	7.3
Relative evaporation rate (butyl acetate=1):	<1 Slower
Melting point:	>32 ° F
Boiling point:	>210.2 ° F
Auto-ignition temperature:	430 ° C (806 ° F)
Decomposition temperature:	Not Determined
Flammability (solid, gas):	Not Applicable
Vapor pressure:	17 mm Hg @ 20 ° C
Flash Point:	Not Applicable
Flash Point Method:	Not Applicable
Relative vapor density @ 20 ° C:	Heavier than air
Relative density:	1.07
Density:	8.91 lbs / gal
Solubility:	Diluted with water
Log Pow:	Not available
Log Kow:	Not available
Viscosity, kinematic:	Not available
Viscosity, dynamic:	1,000-3,500 mPa.s
Explosive properties:	Non-explosive
Oxidizing properties:	None known
Explosive limits:	Not Applicable

Other information:

No further relevant information available

Section 10: Stability and reactivity

Reactivity

Hazardous polymerization does not occur

Chemical Stability

Product is stable under normal storage conditions

Conditions to Avoid

Protect from freezing conditions

Incompatible Materials

No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Section 11: Toxicological information

Information on toxicological effects

TOXICITY MEASURES:

Acute Oral Toxicity: LD50 rat: >5,000 mg/kg

Primary routes of exposure:

Routes of entry are ingestion and inhalation, but may include eye or skin contact.

Acute toxicity:

Assessment of acute toxicity: Virtually non-toxic after a single ingestion. Virtually non-toxic after a single skin contact. Virtually non-toxic after inhalation. Ingestion may cause gastrointestinal disturbances.

ATE Oral LD50: >5000 mg-kg

ATE Dermal LD50: >2000 mg/kg

Benzyl Alcohol: Oral Rat LD50: 1620 mg/kg; Dermal Rabbit LD50: >2000mg/kg; Inhalation RAT LC50: >4178 mg/m³ 4 HR *Monoethanolamine*: Oral rat LD50: 10.2 g/kg; Dermal rat:1025 mg/kg

Chronic toxicity:

No delayed chronic test data are known

Other information:

The product is considered to be harmless to health if used in the correct manner

Section 12: Ecological information

All work practices must be aimed at eliminating environmental contamination.

Toxicity

As far as present knowledge, the product is non-toxic

Persistence and degradability

The product can be virtually eliminated from water by abiotic processes e.g. adsorption onto activated sludge.

Bioaccumulation:

Accumulation in organisms is not to be expected

Mobility

No data available

Other adverse effects

Not determined for this product

Section 13: Disposal considerations

Waste treatment methods

Regional legislation (waste):

Dispose of waste and unused contents in accordance with national and local regulations.

Waste disposal recommendations:

Ensure the use of properly authorized waste management companies where appropriate or uncertain.

Section 14: Transport information

The product is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and therefore no classification is required.

Section 15: Regulatory information

U.S. Federal Regulations

U.S. OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations

U.S SARA Reporting Requirements:

The following components of this product are subject to reporting requirements of sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

CHEMICAL	SECTION 302 EHS (TPQ) (40 CFR 355, Appendix A)	SECTION 304 RQ (40 CFR Table 302.4)	SECTION 313 TRI (40 CFR 372.65)
----------	---	--	------------------------------------

Not considered hazardous

A Section 311/312 (40 CFR 370) Hazard Categories:

ACUTE: No; CHRONIC: Yes; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

Toxic Substances Control Act (TSCA):

All components of this product are included on the TSCA inventory

U.S. CERCLA Reportable Quantity (RQ):

This product is not listed under CERCLA

U.S. Clean Air Act Threshold Quantity (TQ):

This product is not listed.

U.S. Clean Water Act Requirements:

This product is not listed

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Canadian WHMIS Classification:

.

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

European Inventory of Existing Chemicals (EINECS):

All of the components of this product are included on EINECS

Section 16: Other information

Indication of changes:

Other information:

Full text of H phrases:



NFPA health hazard: 1-May be irritating

NFPA fire hazard: 0-Not combustible

NFPA reactivity: 0-Normally stable, even under fire exposure conditions, and not reactive with water

Notice to Reader

The information provided herein is believed to be accurate at the time of preparation or prepared from sources deemed to be reliable, but it is the full responsibility of the user to investigate and comprehend other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Acrylux Paint Manufacturing Co., **makes no warranty, expressed or implied, concerning the product or merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by** Acrylux Paint Manufacturing Co., except that the product shall conform to Acrylux Paint Manufacturing Co.,

