



# TECHNICAL DATA SHEET

<b>Product Name:</b>	Colorback Water Based Paver Sealer
<b>Product Numbers:</b>	CBW1, CBW5
<b>Description:</b>	Colorback Water Based Paver sealer is a clear sealer used to enhance and protect pavers and other cementitious surfaces from UV degradation, mold and mildew growth, dirt pick-up, and general wear and tear.
<b>Suggested Uses:</b>	A low luster clear coat for pavers, bricks, and concrete.
<b>Colors:</b>	Clear
<b>Finish:</b>	Satin/Semi-Gloss
<b>Vehicle Type:</b>	Acrylic
<b>Solvent Type:</b>	Water
<b>VOC:</b>	<50 gm/l
<b>Flash Point:</b>	Non-Flammable
<b>Solids by Volume:</b>	37% +/-
<b>Weight Per Gallon:</b>	7.74 lbs. per gal. +/-
<b>Coverage:</b>	Theoretical coverage is 300 square feet per gallon (Spraying) or 400 square feet per gallon (Rolling) depending on the surface porosity. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.

<b>Recommended Dry Time:</b>	At 70 F and 50% relative humidity: Dry to touch in 1-2 hours (depending on weather). Recoat in 3 to 6 hours. The surface will be tack free in 3 to 6 hours, ready for foot traffic in 12 to 24 hours and vehicular traffic in 72 hours. Dry times may vary depending on air temperature, wind, and humidity.
<b>Surface Preparation:</b>	Pavers must be clean, dry and free of any dirt, stains, and failed sealer. On concrete, the surface must be clean and dry. Testing of the surface is recommended to ensure desired results.
<b>Mixing:</b>	Stir well and apply as it comes from the container.
<b>Application:</b>	Apply with a brush, roller (max 3/8" nap), or sprayer. DO NOT APPLY excessive pressure on the roller. Roll with light to medium pressure. Apply paver sealer evenly and do not leave puddles or roller marks. Only one coat is required. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness – DO NOT APPLY THIS PRODUCT. If there has been a skid texture added to the base coat this product may perform properly but all precautions must be taken. Surface should be dry for 24 hours before application.
<b>Packaging:</b>	1 Gallon, 5 Gallon
<b>Shelf Life:</b>	2 Years
<b>Safety Information:</b>	Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a> .