



PRODUCT NAME: Tint-Seal

PRODUCT NUMBERS: TS1, TS5

DESCRIPTION: A one-component urethane penetrating tint sealer.

SUGGESTED USES: A one-component urethane sealer used to change or enhance the color of

pavers and provide them with a UV-resistant, protective, rejuvenated

coating.

ADDITIONAL USES: Roof Tiles

COLOR: Light Yellow

FINISH: Satin/Semi-Gloss

VEHICLE TYPE: Urethane Acrylic

SOLVENT TYPE: Water

VOC: ≤ 50

WEIGHT PER GALLON: 8.1 lbs.

SOLIDS BY % 35%

COVERAGE: Coverage depends on the porosity of the pavers. Spraying

(Recommended) – 250-300 sq. ft. per gallon.

RECOMMENDED DRY TIME: At 70°F and 50% relative humidity: Touch - 1 hour (depending on

weather). **Recoat** – 2 hours. Surface will be tack free in 1 hour, ready for foot traffic in 2 hours and vehicle traffic in 72 hours. Dry times may vary

depending on air temperature, wind, and humidity.

LIMITATIONS: CAUTION: DO NOT apply in temperatures below 50°F. DO NOT apply

to a damp surface. On excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly, causing trapped vapors to bubble. If this occurs, we recommend application during a cooler

time of day.

SURFACE PREPARATION: Pavers must be clean, dry, and free of any dirt, stains, and failed sealer.

On bare concrete, the surface must be clean and dry.

MIXING: Mix Tint-Seal Color Pack in the sealer for two minutes directly before use.

If the mixture is allowed to sit, mix again before use.

APPLICATION: For the most uniform application, apply with an airless sprayer. If a pump

sprayer is used, ensure that it reaches full atomization.

SHELF LIFE: 2 years

PACKAGING: 1 gallon, 5 gallon

DEPARTMENT OF: TRANSPORTATION Not Regulated

SAFETY INFORMATION:

Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush your eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children.